

GE05 / GM10

Escalator and moving walkway

Public transport and commercial configurations at 30° and 35°, and horizontal or inclined walkways to 43.47 m of run.

RANGE

SERIES	SEGMENT	MAX. SPEED	MAX. TRAVEL	MAX. LOAD
E200	Escalator, commercial	0.75 m/s	16 m	30° / 35°
E300	Escalator, high traffic	0.75 m/s	16 m	30° / 35°
E500	Escalator, public transport	0.75 m/s	16 m	30° / 35°
M200	Moving walkway	0.65 m/s	43.47 m	0° / 10° / 11° / 12°

STANDARD FUNCTIONS

- VVVF traction and door drive
- Full collective selective control
- Micro leveling and car position auto-correction
- Light curtain door protection
- Overload protection
- Ascending overspeed protection
- Unintended car movement protection
- Return to base floor at fire emergency

AVAILABLE ON SPECIFICATION

- Automatic rescue device
- Energy regeneration
- Group and peak service control
- Wired and wireless remote monitoring
- Internet of Things reporting
- Seismic sensor
- Cabin air purification
- 18.5 and 23 inch multimedia display

Every configuration includes unintended-movement and ascending-overspeed protection as standard. Full certification in the Download Center.

Weston

Vertical movement and infrastructure engineering

Full range

Technical sheets and certification in the Download Center